



Recessed rear door is fully vented.



features

- **Description:** The fully-vented, steel rear door is made for use with Lowell rack series: LER, LGR, LSER, LSGR, and LPR. The full-vent pattern allows enhanced front-to-rear air flow when the rack features a fully-vented front door or open front. The fully-vented rear door is ideal for racks loaded with electronics, like amplifiers or servers, that have self-contained cooling fans.
- **Ordering:** To order a rack with the fully-vented rear door instead of a standard rear door (with top/bottom vents), order the "LRD" rack model (less rear door), then order the fully-vented rear door separately.
- **Construction:**
 - 16-gauge steel with black wrinkle powder epoxy finish
 - 19.875"W x .687"D
 - Integral recessed handle
 - Keyed lock (keyed differently than front door)
 - Made in the U.S.A. with certified U.S. steel
- **Mounting:** Mounts with right- or left-hand swing (field changeable) with spring-loaded hinge pins.
- **Optional:** (order separately)
 - **Keyless Latch:** #TLK thumb-turn cam latch replaces key lock cylinder, enabling the door to stay closed without locking it.

a&e specifications

The rear door shall be Lowell Model _____, which shall be 16-gauge steel with black wrinkle powder epoxy finish. The door shall be fully-vented. It shall mount with left- or right-swing, using spring-loaded hinge pins. The door shall feature a recessed handle and key lock.

LRD-FV series summary

Rear Door Model No.	For Rack Panel Space	Height	Width	Depth
LRD-35FV	35U	61.19 [1554]	19.875 [505]	0.687 [17]
LRD-40RV	40U	69.94 [1776]	19.875 [505]	0.687 [17]
LRD-44FV	44U	76.94 [1954]	19.875 [505]	0.687 [17]

1 rack unit = 1.75 in. [44.45 mm]



