



DESCRIPTION:

Model ACR-1507-GNLT power distribution panel with gooseneck lights features 15A NEMA outlets (seven total). The front has one unswitched outlet (always on). The rear has three duplex (two duplex are always on, one duplex is controlled by the switch which is lighted, making it easy to see at-a-glance when the switched outlets are powered).

The panel features three XLR connectors. Two front connectors are controlled by a dimmer, while the rear connector is controlled by a separate on/off switch. The panel ships with two gooseneck style lights to mount to the connectors. A third light can be ordered as an option if three lights are needed.

The compact steel chassis with black powder epoxy finish is designed to occupy minimal rack space with overall dimensions of 19"W x 9"D x 1.75"H (1U). Termination is via a detachable nine foot power cord with NEMA 5-15P plug.

A&E SPECIFICATIONS:

The rack shall include Lowell panel ACR-1507-GNLT, which shall feature two gooseneck lights and three XLR connectors—two in front controlled by a dimmer and one in back controlled by a separate on/off switch. The panel shall feature a total of seven 15A NEMA outlets, two of which shall be controlled by the lighted power switch. The other outlets, including one in front, shall be unswitched (always on). Power rating shall be 120VAC, 60Hz, 15A, 1800W. Termination shall be via a detachable 9 ft. cord with NEMA 5-15P plug.

FEATURES:

- **Outlets:** Unit features a total of seven 15A NEMA outlets, which are either switched (controlled by switch) or unswitched (always on).
 - Front Outlets:
 - NEMA 5-15R (1 unswitched single)
 - Rear Outlets:
 - NEMA 5-15R (1 switched duplex, 2 unswitched duplex)
- **Rocker Switch:** A lighted rocker switch in the front of the panel controls power to the switched outlets.
- **Gooseneck Lights:** The panel includes two gooseneck lights (12VDC, 40mA). Each light has four LEDs to produce a soft white light.
- **XLR Connectors:** The panel has two XLR connectors in front, which are controlled by the dimmer. Another XLR connector in the rear is controlled by a separate on/off switch.
- **Power Rating:** 120VAC, 60Hz, 15A, 1800W
- **Circuit Breaker Protection:** 15A breaker in switch
- **Power Cord:** Detachable 9-ft. cord with NEMA 5-15P plug
- **Chassis:** 19"W x 9"D x 1.75"H (1U), 9 lbs.
- **Certification:** ETL Listed in US/Canada (UL60065)
- **Country of Origin:** Made in U.S.A. with global components
- **Optional:**
 - GNLT-18: Single gooseneck style light

ACR Series Power Distribution Panels

Model No.	Power Rating	Front Outlets	Rear Outlets	Surge Supp.	Power Input	Switch Type	Outlets Controlled by Switch	Network Interface	Charging Ports	Time Delay	Input from Remote Switch	Input from External Trigger	Input from Alarm System	Output to Remote Control	Lights	Country of Origin
ACR-1505-SSI-RC	15A	1 (15A)	4 (15A)	yes	6' cord	---	---	yes	rear	---	---	---	---	---	---	USA
ACR-1506-LTS	15A	---	6 (15A)	yes	9' cord	rocker	all	---	---	---	---	---	---	---	hd	USA
ACR-1507-GNLT	15A	1 (15A)	6 (15A)	---	9' det.cord	rocker	2	---	---	---	---	---	---	---	goose	USA
ACR-1507-HDLT	15A	1 (15A)	6 (15A)	---	9' det.cord	rocker	2	---	---	---	---	---	---	---	hd-nt	USA
ACR-1507-SSI-FC	15A	1 (15A)	6 (15A)	yes	6' cord	---	---	yes	front	---	---	---	---	---	---	USA
ACR-1508-SHW	15A	---	8 (15A)	yes	6' conduit	---	---	---	---	---	---	---	---	---	---	USA
ACR-1509-S	15A	1 (15A)	8 (15A)	yes	9' cord	rocker	3	---	---	---	---	---	---	---	---	China
ACR-159-S	15A	1 (15A)	8 (15A)	yes	9' cord	rocker	all	---	---	---	---	---	---	---	---	China
ACR-2009	20A	1 (15A)	8 (15/20A)	---	9' cord	rocker	5	---	---	---	---	---	---	---	---	USA
ACR-209-S	20A	1 (20A)	8 (20A)	yes	9' cord	rocker	all	---	---	---	---	---	---	---	---	China
ACR-RPC-1508-SD	15A	---	8 (15A)	yes	9' cord	ext	6	---	---	---	yes	yes	yes	---	---	USA
ACR-SEQ4-1509	15A	1 (15A)	8 (15A)	---	9' cord	rocker & ext	6	---	---	SEQ	yes	---	yes	---	---	USA
ACR-SEQ6-2009	20A	1 (15A)	8 (15A)	---	9' cord	rocker & ext	6	---	---	SEQ	yes	---	yes	yes	---	USA

Surge Suppression = Panel includes basic surge suppression. (For rackmount panels with advanced surge suppression see ACSPR Series.)

Power Input = cord (attached cord), det.cord (detachable cord), conduit (non-metallic flexible conduit)

Switch Type (activation) = rocker (rocker switch on front), ext (external switch, not included)

Outlets Controlled by Switch = Number of outlets activated/deactivated by switch. Other outlets are unswitched (always on).

Network Interface = Panel includes network pass-through ports.

Charging Ports = Panel includes high speed charging connectors for devices (USB-A, Type-C)

Time Delay (SEQ) = Panel includes sequencing to activate/deactivate switched outlets with a time delay between steps (adjustable).

Input from Remote Switch = Panel can be controlled by an external switch, typically placed in a remote location (order RPS Series switch separately).

Input from External Trigger = Panel can be controlled by external trigger voltage (separate control system by others, not included).

Input from Alarm System = Panel can accept control override from an alarm system (alarm by others, not included).

Output to Remote Control = Panel can activate/deactivate remote equipment (order RPC Series remote power controls separately).

Lights = hd (hooded white light), goose (gooseneck lights), hd-nt (hooded night-vision lights)

See individual product spec sheets for more information.

