



DESCRIPTION:

Model ACR-1507-HDLT power distribution panel features 15A NEMA outlets (seven total) plus hooded night vision lighting, which changes from red to white as the dimmer control increases intensity. The panel also has an XLR connector in the rear, which can be used to add an (optional) gooseneck light.

The front panel features one single unswitched outlet (always on), while the rear has three duplex outlets (one duplex is controlled by the switch; two duplexes are always on). All outlets are clearly marked to assist the integrator with connections. The power switch is lighted, which makes it easy to see at-a-glance when the switched outlets are powered.

The compact steel chassis with black powder epoxy finish is designed to occupy minimal rack space with overall dimensions of 19"W x 9"D x 1.75"H (1U). Termination is via a detachable nine foot power cord with NEMA 5-15P plug.

A&E SPECIFICATIONS:

The rack shall include Lowell panel ACR-1507-HDLT, which shall feature two hooded lights with a dimmer control. Hooded lights shall be night vision friendly with red light changing to white as intensity increases. The panel shall have a power rating of 120VAC, 60Hz, 15A, 1800W and feature one 15A NEMA outlet in the front and three 15A NEMA duplex in the rear. One of the rear duplexes shall be controlled by the switch; other outlets shall be unswitched (always on). The panel shall feature an XLR connector in the rear for use with an (optional) gooseneck light. The 19"W x 9"D x 1.75" (1U) rackmount panel shall include a detachable 9 ft. cord with NEMA 5-15P plug.

FEATURES:

- **Outlets:** Unit features a total of seven 15A NEMA outlets, which are either switched (controlled by front switch) or unswitched (always on).
 - Front Outlets: NEMA 5-15R (1 unswitched single)
 - Rear Outlets: NEMA 5-15R (1 switched duplex, 2 unswitched duplex)
- **Rocker Switch:** A lighted rocker switch in the front of the panel controls power to the switched outlets.
- **Night Vision Hooded Lights with Dimmer Control:** Energy efficient LEDs with overhanging hoods provide long life and are not prone to breakage like incandescent bulbs. Light changes color from red to white as intensity increases.
- **Power Rating:** 120VAC, 60Hz, 15A, 1800W
- **Circuit Breaker Protection:** 15A breaker in switch
- **Power Cord:** Detachable 9-ft. cord with NEMA 5-15P plug
- **Chassis:** 19"W x 9"D x 1.75"H (1U), 9 lbs.
- **Certification:** ETL Listed in US/Canada (UL60065)
- **Country of Origin:** Made in U.S.A. with global components
- **XLR Connector:** A rear XLR connector with on/off switch can be used to add an optional gooseneck light (order separately).
- **Optional:**
 - GNLT-18: Single gooseneck light

ACR Series Power Distribution Panels

Model No.	Power Rating	Front Outlets	Rear Outlets	Surge Supp.	Power Input	Switch Type	Outlets Controlled by Switch	Network Interface	Charging Ports	Time Delay	Input from Remote Switch	Input from External Trigger	Input from Alarm System	Output to Remote Control	Lights	Country of Origin
ACR-1505-SSI-RC	15A	1 (15A)	4 (15A)	yes	6' cord	---	---	yes	rear	---	---	---	---	---	---	USA
ACR-1506-LTS	15A	---	6 (15A)	yes	9' cord	rocker	all	---	---	---	---	---	---	---	hd	USA
ACR-1507-GNLT	15A	1 (15A)	6 (15A)	---	9' det.cord	rocker	2	---	---	---	---	---	---	---	goose	USA
ACR-1507-HDLT	15A	1 (15A)	6 (15A)	---	9' det.cord	rocker	2	---	---	---	---	---	---	---	hd-nt	USA
ACR-1507-SSI-FC	15A	1 (15A)	6 (15A)	yes	6' cord	---	---	yes	front	---	---	---	---	---	---	USA
ACR-1508-SHW	15A	---	8 (15A)	yes	6' conduit	---	---	---	---	---	---	---	---	---	---	USA
ACR-1509-S	15A	1 (15A)	8 (15A)	yes	9' cord	rocker	3	---	---	---	---	---	---	---	---	China
ACR-159-S	15A	1 (15A)	8 (15A)	yes	9' cord	rocker	all	---	---	---	---	---	---	---	---	China
ACR-2009	20A	1 (15A)	8 (15/20A)	---	9' cord	rocker	5	---	---	---	---	---	---	---	---	USA
ACR-209-S	20A	1 (20A)	8 (20A)	yes	9' cord	rocker	all	---	---	---	---	---	---	---	---	China
ACR-RPC-1508-SD	15A	---	8 (15A)	yes	9' cord	ext	6	---	---	---	yes	yes	yes	---	---	USA
ACR-SEQ4-1509	15A	1 (15A)	8 (15A)	---	9' cord	rocker & ext	6	---	---	SEQ	yes	---	yes	---	---	USA
ACR-SEQ6-2009	20A	1 (15A)	8 (15A)	---	9' cord	rocker & ext	6	---	---	SEQ	yes	---	yes	yes	---	USA

Surge Suppression = Panel includes basic surge suppression. (For rackmount panels with advanced surge suppression see ACSPR Series.)

Power Input = cord (attached cord), det.cord (detachable cord), conduit (non-metallic flexible conduit)

Switch Type (activation) = rocker (rocker switch on front), ext (external switch, not included)

Outlets Controlled by Switch = Number of outlets activated/deactivated by switch. Other outlets are unswitched (always on).

Network Interface = Panel includes network pass-through ports.

Charging Ports = Panel includes high speed charging connectors for devices (USB-A, Type-C)

Time Delay (SEQ) = Panel includes sequencing to activate/deactivate switched outlets with a time delay between steps (adjustable).

Input from Remote Switch = Panel can be controlled by an external switch, typically placed in a remote location (order RPS Series switch separately).

Input from External Trigger = Panel can be controlled by external trigger voltage (separate control system by others, not included).

Input from Alarm System = Panel can accept control override from an alarm system (alarm by others, not included).

Output to Remote Control = Panel can activate/deactivate remote equipment (order RPC Series remote power controls separately).

Lights = hd (hooded white light), goose (gooseneck lights), hd-nt (hooded night-vision lights)

See individual product spec sheets for more information.

