



features.

- **Overall Height:** 2.5" [64] slightly more than 1U
- **Overall Width:** 19.00" [483]
- **Shelf Width:** 17.50" [445]
- **Shelf Depth:** 14.625" [371] 14.00" max. shelf extension
- **Description:** Rackmount shelf slides out and latches securely in the open position to stay in place while you work on equipment. Latches securely closed when finished.
- **Construction:**
 - 16-gauge certified U.S. steel
 - Smooth black powder epoxy finish
 - Includes rear support brackets
- **Mounting:**
 - Requires 4-point mounting.
 - Brackets are typically mounted to rear rails, (minimum rear support extension = 14.88", maximum rear support extension = 23.50".
 - Brackets can also be mounted sideways (maximum width = 26.50").
- **Cable Management:**
 - Rear lacing points
- **Load Capacity:** 50 lbs.
- **Origin:** Made in the U.S.A.

a&e specifications.

The rackmount shelf shall be Lowell Model #SLS, capacity shall be 50 lbs. The shelf shall be made in the U.S.A. which shall be 16-gauge certified U.S. steel with black powder epoxy finish. Overall dimensions shall be 2.5"H x 14.88"D x 19"W. It shall include two rear support brackets for four point mounting. The shelf shall be designed to slide forward and latch securely in the open or closed position. Load

Model summary

Model No.	Overall Height	Shelf Width	Shelf Depth	Overall Width	Load Capacity	Material	Weight	Carton Pack
▶ SLS	2.5" [64]	17.50" [445]	14.625 [371]	19.00 [483]	50 lbs. [23 kg]	16-ga. steel	13 lbs. [5.8 kg]	1

Dimensions = inches [mm]; 1U = 1.75"

