



Volume control with standard wall plate provides precise level adjustment of single or multiple speakers.

**FEATURES:**

- Type: Mono autoformer attenuator with rotary switch
- Power Rating: 10W
- Attenuation: 3dB per step (33dB total), two steps of 6dB each before off
- Phoenix style plug-in termination strips for pre-wire convenience
- Wire capacity to 14 gauge
- Standard one-gang wall plate, stainless steel
- Printed scale for rotary dial features 10 volume positions plus OFF (0)
- Fluted rotary knob
- Mounts in one-gang E.O. box with minimum depth of 2.125" (not included)
- For use with 25V/70V/100V speaker line
- Country of Origin: China

**A&E SPECIFICATIONS:**

The volume control shall be Lowell model 10LVC, which shall have a 10W power rating and attenuation of 3dB per step with two steps of 6dB each before off. The volume control shall include a one-gang wall plate with stainless steel finish and printed scale. The unit shall be able to mount in an E.O. box with minimum inside dimensions of 1.875" x 2.688" x 2.125".

Summary

Model No.	Power Rating	Attenuation	Type	Switch	Style	Color	For Use With
<b>10LVC</b>	<b>10W</b>	<b>3dB steps *</b>	<b>Auto-trans</b>	<b>Rotary</b>	<b>Standard Wall Plate</b>	<b>SS</b>	<b>25V/70V/100V Speaker Line</b>

\* 33dB total; two steps of 6dB each before off

