



Notches on the shelf's rear flange make it easy to mount a 12" power strip (see options).



Some models are available in multi-pack cartons.

### features.

- **Panel Space:** 2U
- **Overall Depth:** 10.75" [273]
- **Overall Width:** 19.00" [483]
- **Usable Width:** 17.56" [446]
- **Description:** Steel utility shelf with solid base mounts to 19" E.I.A. compliant rack to support non-rackmount equipment such as consumer electronics, power supplies, or chassis style components. The US Series shelf is available in two depths and multiple heights (see chart below).
- **Construction:** Single piece 16-gauge certified U.S. steel construction.
- **Finish:** Smooth black powder epoxy finish
- **Base:** Solid
- **Front:** Front flange (0.375") adds strength and helps keep equipment in place.
- **Rear:** Slotted rear flange (0.56") provides tie-off points for cable management and notches to mount an optional 12" power strip.
- **Load Capacity:** 50 lbs. [22.6 kg]
- **Origin:** Made in the U.S.A.
- **Options:** (order separately)
  - **ACS-1506-WW:** Compact 12" AC power strip with six 15A NEMA outlets, spaced for power supplies, and 6 ft. attached cord.
  - **ACS-1507:** Compact 12" AC power strip with seven 15A NEMA outlets and 6 ft. detachable cord.

### a&e specifications.

The rackmount utility shelf shall be Lowell model #US-210 with overall dimensions of 19"W x 10.75"D x 2U. It shall be 16-gauge certified U.S. steel construction with solid base and smooth black powder epoxy finish. It shall feature a front and rear flange. The rear flange shall have slots to provide tie-off points for cable management, and

notches to mount an optional 12" power strip. The shelf shall be made in the U.S.A. and have a load capacity of 50 lbs.

### US series summary

| Model No.                 | Panel Space | Overall Depth      | Overall Width      | Usable Width       | Load Capacity          | Material            | Finish              | Quantity |
|---------------------------|-------------|--------------------|--------------------|--------------------|------------------------|---------------------|---------------------|----------|
| <b>Single Shelves</b>     |             |                    |                    |                    |                        |                     |                     |          |
| US-110                    | 1 U         | 10.75 [273]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 1        |
| <b>US-210</b>             | <b>2 U</b>  | <b>10.75 [273]</b> | <b>19.00 [483]</b> | <b>17.56 [446]</b> | <b>50 lbs. [23 kg]</b> | <b>16-ga. steel</b> | <b>Smooth Black</b> | <b>1</b> |
| US-310                    | 3 U         | 10.75 [273]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 1        |
| US-114                    | 1 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 1        |
| US-214                    | 2 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 1        |
| US-314                    | 3 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 1        |
| US-414                    | 4 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 1        |
| <b>Multi-pack cartons</b> |             |                    |                    |                    |                        |                     |                     |          |
| US-110CC                  | 1 U         | 10.75 [273]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 12       |
| US-110MC                  | 1 U         | 10.75 [273]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 50       |
| <b>US-210CC</b>           | <b>2 U</b>  | <b>10.75 [273]</b> | <b>19.00 [483]</b> | <b>17.56 [446]</b> | <b>50 lbs. [23 kg]</b> | <b>16-ga. steel</b> | <b>Smooth Black</b> | <b>6</b> |
| US-114CC                  | 1 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 10       |
| US-114MC                  | 1 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 50       |
| US-214CC                  | 2 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 6        |
| US-214MC                  | 2 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 50       |
| US-314MC                  | 3 U         | 14.00 [356]        | 19.00 [483]        | 17.56 [446]        | 50 lbs. [23 kg]        | 16-ga. steel        | Smooth Black        | 36       |

Dimensions = inches [mm]; 1U = 1.75"



