



Notches on the shelf's rear flange make it easy to mount a 12" power strip (see options).

### features.

- **Panel Space:** 3U
- **Overall Depth:** 10.75" [273]
- **Overall Width:** 19.00" [483]
- **Usable Width:** 17.56" [446]
- **Description:** Steel utility shelf with solid base mounts to 19" E.I.A. compliant rack to support non-rackmount equipment such as consumer electronics, power supplies, or chassis style components. The US Series shelf is available in two depths and multiple heights (see chart below).
- **Construction:** Single piece 16-gauge certified U.S. steel construction.
- **Finish:** Smooth black powder epoxy finish
- **Base:** Solid
- **Front:** Front flange (0.375") adds strength and helps keep equipment in place.
- **Rear:** Slotted rear flange (0.56") provides tie-off points for cable management and notches to mount an optional 12" power strip.
- **Load Capacity:** 50 lbs. [22.6 kg]
- **Origin:** Made in the U.S.A.
- **Options:** (order separately)
  - **ACS-1506-WW:** Compact 12" AC power strip with six 15A NEMA outlets, spaced for power supplies, and 6 ft. attached cord.
  - **ACS-1507:** Compact 12" AC power strip with seven 15A NEMA outlets and 6 ft. detachable cord.

### a&e specifications.

The rackmount utility shelf shall be Lowell model #US-310 with overall dimensions of 19"W x 10.75"D x 3U. It shall be 16-gauge certified U.S. steel construction with solid base and smooth black powder epoxy finish. It shall feature a front and rear flange. The rear flange shall have slots to provide tie-off points for cable management, and

notches to mount an optional 12" power strip. The shelf shall be made in the U.S.A. and have a load capacity of 50 lbs.

### US series summary

Model No.	Panel Space	Overall Depth	Overall Width	Usable Width	Load Capacity	Material	Finish	Quantity
<b>Single Shelves</b>								
US-110	1 U	10.75 [273]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-210	2 U	10.75 [273]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
<b>US-310</b>	<b>3 U</b>	<b>10.75 [273]</b>	<b>19.00 [483]</b>	<b>17.56 [446]</b>	<b>50 lbs. [23 kg]</b>	<b>16-ga. steel</b>	<b>Smooth Black</b>	<b>1</b>
US-114	1 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-214	2 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-314	3 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-414	4 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
<b>Multi-pack cartons</b>								
US-110CC	1 U	10.75 [273]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	12
US-110MC	1 U	10.75 [273]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	50
US-210CC	2 U	10.75 [273]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	6
US-114CC	1 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	10
US-114MC	1 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	50
US-214CC	2 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	6
US-214MC	2 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	50
US-314MC	3 U	14.00 [356]	19.00 [483]	17.56 [446]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	36

Dimensions = inches [mm]; 1U = 1.75"



