



Volume control with adhesive dial scale for rackmount use provides precise level adjustment of single or multiple speaker lines.

FEATURES:

- Mono autoformer attenuator with rotary switch for use with 25V/70V/100V speaker line
- 100W power rating
- Switch positions Off–10
- 1.5dB per step attenuation (13.5dB total)
- Phoenix style plug-in screw termination strips for pre-wire convenience
- Wire capacity to 14 gauge
- Includes control assembly with knob, and an adhesive label with dial scale (and plastic window for a paper label).
- ETL Listed
- Assembled in the U.S.A.

A&E SPECIFICATIONS:

The ETL Listed volume control shall be Lowell model 10015LVC-RM, which shall have a 100W power rating and 1.5dB per step attenuation (13.5dB total). It shall feature phoenix style plug-in screw termination strips for pre-wire and up to 14 gauge wire capacity. The volume control shall include a rotary knob and an adhesive label with dial scale.

OPTIONS: (order separately)

- LVC8P-ID-2: 19" x 2U rack panel to hold multiple volume controls features a rear lacing flange and pocket window for a paper label.

10015LVC Series Attenuator Summary

Model No.	Power Rating	Attenuation *	Type	Switch	Style	Color	For Use With
10015LVC	100W	1.5dB steps	Auto-trans	Rotary	Standard Wall Plate	SS	25V/70V/100V Speaker Line
10015LVC-SW	100W	1.5dB steps	Auto-trans	Rotary	Standard Wall Plate	White	25V/70V/100V Speaker Line
10015LVC-DA	100W	1.5dB steps	Auto-trans	Rotary	Decorator Wall Plate	Almond	25V/70V/100V Speaker Line
10015LVC-DB	100W	1.5dB steps	Auto-trans	Rotary	Decorator Wall Plate	Black	25V/70V/100V Speaker Line
10015LVC-DW	100W	1.5dB steps	Auto-trans	Rotary	Decorator Wall Plate	White	25V/70V/100V Speaker Line
10015LVC-RM	100W	1.5dB steps	Auto-trans	Rotary	Adhesive Label **	Black	25V/70V/100V Speaker Line

This spec ▶

* 13.5 dB total

** For rackmount panel

WIRING & SCHEMATIC:

