



features

- **Description:** Steel raceway for Lowell slim frame racks is a three-piece assembly engineered to provide extra wiring space between racks or at the end of a multi-bay configuration. Each cable chase features 3" [76mm] of useable space, bolt-on front/rear/top, and joining hardware.
- **Construction:**
 - 16 gauge steel raceway
 - 3" [76mm] channel depth
 - Black powder epoxy finish
 - For use with LXR or LVR Series slim frame rack with racking space of 44U and depth of 26.25"
 - Top piece features compound knockouts (2"-1" or 51-25mm).
 - When used on a single rack or at the end of a bay, closure can be accomplished using an optional side panel.
- **Origin:** Made in the U.S.A.
- **Ships unassembled.** Assemble without field-drilling using 10-32 nuts and bolts provided. Insert four bolts through channel assembly to secure to rack. (If a side panel is used it mounts to keyhole slots in the channel.)

a&e specifications

The cable chase for Lowell 44U slim frame racks shall be Model No. LXR-4426CC3, which shall provide 3" [76mm] of cable management space on the side of the specified rack. Field-mounting shall be accomplished without drilling using 10-32 nuts and bolts provided. The channel shall be 16 gauge steel with a black powder epoxy finish and shall feature compound knockouts on top.

**Note: When the raceway is used with a variable depth rack (LVR Series), the rack depth must be set to 26.25".*



MADE IN THE USA



CERTIFIED US STEEL

Series summary

| Model No. | Description | Racking Height | Overall Height | Channel Depth | Overall Depth | For use with Rack Model |
|---------------|-------------|----------------|-----------------|---------------|----------------|-------------------------|
| LXR-4421CC3 | Cable chase | 44U | 80.65" / 2049mm | 3" / 76mm | 21.94" / 557mm | 21.00" / 533mm |
| ▶ LXR-4426CC3 | Cable chase | 44U | 80.65" / 2049mm | 3" / 76mm | 27.19" / 691mm | 26.25" / 660mm |

One rack unit (RU or U) = 1.75 inches or 44.45 mm.



