



### features . . . . .

- **Description:** Steel raceway for Lowell slim frame racks is a three-piece assembly engineered to provide extra wiring space between racks or at the end of a multi-bay configuration. Each cable chase features 3" [76mm] of useable space, bolt-on front/rear/top, and joining hardware.
- **Construction:**
  - 16 gauge steel raceway
  - 3" [76mm] channel depth
  - Black powder epoxy finish
  - For use with LXR or LVR Series slim frame rack with racking space of 44U and depth of 21.00"
  - Top piece features compound knockouts (2"-1" or 51-25mm).
  - When used on a single rack or at the end of a bay, closure can be accomplished using an optional side panel.
- **Origin:** Made in the U.S.A.
- **Ships unassembled.** Assemble without field-drilling using 10-32 nuts and bolts provided. Insert four bolts through channel assembly to secure to rack. (If a side panel is used it mounts to keyhole slots in the channel.)

### a&e specifications . . . . .

The cable chase for Lowell 44U slim frame racks shall be Model No. LXR-4421CC3, which shall provide 3" [76mm] of cable management space on the side of the specified rack. Field-mounting shall be accomplished without drilling using 10-32 nuts and bolts provided. The channel shall be 16 gauge steel with a black powder epoxy finish and shall feature compound knockouts on top.

*\*Note: When the raceway is used with a variable depth rack (LVR Series), the rack depth must be set to 21.00".*



### Series summary

Model No.	Description	Racking Height	Overall Height	Channel Depth	Overall Depth	For use with Rack Model
LXR-4421CC3	Cable chase	44U	80.65" / 2049mm	3" / 76mm	21.94" / 557mm	21.00" / 533mm
LXR-4426CC3	Cable chase	44U	80.65" / 2049mm	3" / 76mm	27.19" / 691mm	26.25" / 660mm

One rack unit (RU or U) = 1.75 inches or 44.45 mm.



