



Volume control with adhesive dial scale for rackmount use provides precise level adjustment of single or multiple speaker lines.

### FEATURES:

- Mono autoformer attenuator with rotary switch for use with 25V/70V/100V speaker line
- 50W power rating
- Switch positions Off–10
- 3dB per step attenuation (33dB total, two steps of 6dB each before off)
- Phoenix style plug-in screw termination strips for pre-wire convenience
- Wire capacity to 14 gauge
- Includes control assembly with knob, and an adhesive label with dial scale and plastic window for a paper label.
- ETL Listed
- Assembled in the U.S.A.

### A&E SPECIFICATIONS:

The volume control shall be Lowell model 50LVC-RM, which shall have a 50W power rating and attenuation of 3dB per step with two steps of 6dB each before off. It shall include a rotary knob and an adhesive label with dial scale. The volume control shall be ETL Listed.

### OPTIONS: (order separately)

- LVC8P-ID-2: 19" x 2U steel rackmount panel with eight punches to mount standard controls. Panel includes printing for volume levels so adhesive labels (included with some controls) are not needed.
- SEP-2: 19" x 2U steel rackmount panel can be field-punched to mount various controls.

## 50LVC Series Attenuator Summary

Model No.	Power Rating	Attenuation *	Type	Switch	Style	Color	For Use With
50LVC	50W	3dB steps	Auto-trans	Rotary	Standard Wall Plate	SS	25V/70V/100V Speaker Line
50LVC-SA	50W	3dB steps	Auto-trans	Rotary	Standard Wall Plate	Almond	25V/70V/100V Speaker Line
50LVC-SW	50W	3dB steps	Auto-trans	Rotary	Standard Wall Plate	White	25V/70V/100V Speaker Line
50LVC-DA	50W	3dB steps	Auto-trans	Rotary	Decorator Wall Plate	Almond	25V/70V/100V Speaker Line
50LVC-DB	50W	3dB steps	Auto-trans	Rotary	Decorator Wall Plate	Black	25V/70V/100V Speaker Line
50LVC-DW	50W	3dB steps	Auto-trans	Rotary	Decorator Wall Plate	White	25V/70V/100V Speaker Line
<b>50LVC-RM</b>	<b>50W</b>	<b>3dB steps</b>	<b>Auto-trans</b>	<b>Rotary</b>	<b>Adhesive Label **</b>	<b>Black</b>	<b>25V/70V/100V Speaker Line</b>

This spec ▶

\* 33dB total; two steps of 6dB each before off

\*\* For rackmount panel



